

10/615,069

CLAIMS

Please amend the claims as follows:

1. (currently amended) A fiber optic control system comprising:
- 5 an illumination source for producing a light beam;
- a plurality of optical fibers, each fiber arranged to receive a respective portion of the light beam at a coupling end and to conduct the respective portion of the light beam to an illumination end;
- a planar light switch comprising a plurality of light attenuating pixels, the
- 10 light switch positioned between the illumination source and the optical fiber coupling ends, each of the pixels being electronically controllable for selectively coupling portions of the light beam to respective coupling ends of the optical fibers; and
- a plurality of optically operated devices for converting received optical
- 15 signals to corresponding electrical signals~~light-activated circuits~~, each circuit optically operated device optically coupled to the respective illumination end of the optical fiber and responsive to the respective portion of the light beam radiated from the respective illumination end for providing an electrical control signal corresponding to the respective portion of the light beam received by the
- 20 optically operated device for controlling~~to~~ a remotely located device in communication with the optically operated device.
2. (original) The system of claim 1, further comprising a controller coupled to the planar light switch for controlling a light attenuation property of each of the pixels of the planar light switch.
- 25 3. (original) The system of claim 1, wherein the light activated circuit further comprises at least one of a phototransistor, a photo diode, or a photo resistor.

10/615,069

4. (original) The system of claim 1, further comprising a lens positioned between the illumination source and the planar light switch for directing the light beam onto the planar light switch.

5. (original) The system of claim 1, wherein at least one pixel of the planar light switch is aligned with a respective coupling end of at least one optical fiber.

6. (original) The system of claim 1, wherein the planar light switch is a liquid crystal display.

7. (original) The system of claim 1, wherein the illumination source further comprises an electroluminescent light source.

8. (original) The system of claim 1, wherein the illumination source further comprises a semiconductor light source.

9. (original) The system of claim 8, wherein the semiconductor light source is a light emitting diode or a laser semiconductor.

10. (original) The system of claim 8, wherein the semiconductor light source further comprises an array of semiconductor light sources

11. (original) The system of claim 1, further comprising a heat shield mounted between the illumination source and the planar light switch for reducing heat transmitted from the illumination source to the planar light switch.

12. (original) The system of claim 1, wherein the plurality of optical fibers are arranged in a two-dimensional array at respective coupling ends.

10/615,069

13. (currently amended) A method of optically controlling remote devices comprising:

directing a light beam at a first side of a selectively transmissive planar light switch;

5 allowing portions of the light beam to be transmitted through the switch onto respective coupling ends of a plurality of optical fibers positioned for receiving portions of the light beam at a second side of the switch; and

10 optically coupling respective illumination ends of the optical fibers to respective optically operated devices for converting received optical signals to corresponding electrical signals~~light activated circuits~~ so that the portion of the light radiated from the illumination end activates the light activated circuit to generate an electrical control signal corresponding to the portion of the light received by the optically operated device for controlling~~control~~ a remote device in communication with the optically operated device.

15

14. (original) The method of claim 13, wherein the selectively transmissive planar light switch is a liquid crystal display.

15. (original) The method of claim 13, wherein allowing portions of the light beam to be transmitted through the switch further comprises selectively
20 controlling a light attenuation property of each of a plurality of pixels of the light switch.

16. (original) The method of claim 13, further comprising aligning at least one pixel of the light switch with a respective coupling end of at least one optical fiber.

25

17. (cancelled)